



www.trrimstone.com

661.947.1001

PRODUCT DATA

Master Format Spec
SECTION-03 45 00
SECTION- 03 48 00

PRECAST CONCRETE COPING STONE

APPLICATIONS

- Swimming Pool Coping
- Wall Caps
- Wall Base / Wainscot
- Trims
- Coping Stone
- Custom Shapes
- Patio Pavers
- Veneer Stone

COPING SERIES

Genoa Series, La Vella Series, Andora Series, Cantilevered Series, Cordova Series,

DESCRIPTION:

Architectural Pre-Cast concrete is a refined concrete mix and pours into molds to achieve desired shape. Pieces are de-moulded the following day and moist cured for seven days. Architectural Precast Concrete is a superior substitute for natural stones for the fraction of the cost.

STANDARD COLORS & FINISHES

| Alabaster | Vintage Gray | Slate | Tan | Auburn | Truffle | Taupe | Portico | Lt. Beige| | Mushroom|
| Custom Color Mix|

All items come in SAND WASH finish. (Surface is etched to a super fine sand grit to prevent slip)

MIX DESIGN:

SAND	188 LBS
PORTLAND CEMENT	94 LBS
WATER	55 LBS
PEA GRAVEL	133 LBS
SUPERPLASTICIZER	8 oz (as required)
Water / Cement Ratio	0.4

- Portland Cement Type I, per ASTM C150
- Fine Aggregate: Washed Sand per ASTM C33
- Course Aggregate: Pea Gravel per ASTM C33
- Color: Synthetic mineral – oxide pigment per ASTM C979
- Water: Potable, free from deleterious material
- Admixture (superplasticizer) per ASTM C494/C495M Types A – G

Desired PSI: 4000

Limited Warranty:

Product is guaranteed from poor workmanship. This product contains similar properties as normal concrete.

5 Years Structural Warranty Under Normal Usage Conditions

Maintenance:

Product may be sealed after installation. Various concrete or stone water based sealers may be used. Natural look sealers are recommended.

Mild soap with warm water may be used to clean the surface of the product. Other commercially available cleaners may be used. Do a test area before cleaning the entire area. Pressure Washing is NOT recommended, as it may damage the surface.